


TR 410

TECHNICAL CHARACTERISTICS



Euro profile cylinder security lock. Single and double doors. Standard and customised sizes.

DOOR LEAF

- Structure: double galvanised steel sheet (10/10 outer and 10/10 inner) reinforced with internal vertical omega stiffeners.
- Insulation: fireproof material within the door carcass.
- Soft rubber gasket for sealing in between door leaf and door jambs.
- 5 dog bolts.
- 2 robust adjustable welded hinges.
- Lock security plate.
- Wide angle door view.
- Door limiter.
- Adjustable drop seal.
- Internal and external handles available in various types and colors.

FRAME AND SUBFRAME

- Rolled sheet steel frame and subframe with powder coated finish (RAL 8014); 2 mm thickness; available in different colors on request. It is possible to adjust the position of frame and subframe both in height and in depth.

LOCKING SYSTEM

- Euro profile cylinder security lock. Multi-point locking system. Shaped locking bolts.
- Two horizontal locking bolts (upper and lower) one (upper) and three in the centre of the door leaf.
- Cylinder protection device (defender).
- The lock can be equipped with the European profile cylinders 'Smart', 'Excel' and 'Prestige', as well as a half-cylinder for provisional use on site.

COATINGS

- As well as the entire range of standard Torterolo & Re panels, individually designed panels are often specified to ensure that customers' requirements are met. The range of panels includes solid or machined, plain engineered wood finishes and aluminium - the possibilities are endless.
- Removable internal panel keepers.
- Brown external panel keeper surrounds (door edges); other finishes available on request.

VARIETY AND FLEXIBILITY

- Options include overhead fanlights with

either solid or glazed panels (the glazing can be decorative) - including arched fanlights; rectangular or shaped security glass in the leaf; access control: an electronic strike to provide for controlled remote access; arched doors, both single or double; external opener; with fixed side and overhead panels (glazed or solid) for secure entrances.


PERFORMANCE TABLE*

	Burglar Resistance	Thermal Insulation [W/m ² K]	Acoustic Insulation R _w [dB]	Water Tightness	Air Tightness	Wind resistance
SINGLE DOOR	class 3	from 1,8 to 1,3 <i>1,9 with aluminium external panel</i>	from 37 to 42	n.p.d. <i>class 3A with performance kit</i>	class 1 <i>class 3 with performance kit</i>	class C3 <i>class C5 with performance kit</i>
DOUBLE DOOR	class 3	from 2,1 to 1,5 <i>2,2 with aluminium external panel</i>	from 30 to 32	n.p.d. <i>class 0A with performance kit</i>	class 1 <i>class 2 with performance kit</i>	class C3 <i>class C4 with performance kit</i>

n.p.d.: no performance declared

Thermal transmission values given refer to doors covered with plain wooden panels 7mm thick and vary depending on the finishes and options required.

* Torterolo&Re ensures that the construction of the doors is in compliance with prototypes tested in the laboratory. Figures in the table are guaranteed only if the doors are provided by Torterolo&Re complete, fully assembled and covered at its facilities, equipment and dimensions of the products are included within the limits given in "Tabella Limiti" and the doors are adjusted according to the manufacturer's instructions. Unauthorised changes to the product after it's delivery may invalidate performance criteria. For different realizations inquire at its offices.



STANDARD DIMENSIONS Net opening [cm]

	SINGLE DOOR			DOUBLE DOOR					
H	209	209	209	209	209	209	209	209	209
W	79,5	84,5	89,5	110 (79,5+30,5)	115 (84,5+30,5)	120 (89,5+30,5)	120 (79,5+40,5)	125 (84,5+40,5)	130 (89,5+40,5)

Available in standard and customised sizes, single or double doors. For doors with a vertical net opening below 195 cm, the top locking bolt is vertical. Minimum dimensions for secondary leaf - net width of 25 cm.